


Features

- It can realize the customized design scheme
- Excellent amplitude and phase consistency
- Low loss and High isolation

Typical Applications

- Mobile communication field
- GSM,LTE,5G
- Satellite radar, electronic countermeasures
- Test equipment



Electrical&Mechanical Specifications

Parameter		Min.	Typ.	Max.	Units	
Frequency Range		DC		40	GHz	
Insertion Loss			14	15	dB	
Isolation		10	11		dB	
Input VSWR			1.7	1.9	: 1	
Output VSWR			2	2.5	: 1	
Amplitude Imbalance			±0.3	±0.6	dB	
Phase Imbalance			±5	±7	deg	
Power Rating	Forward Power	1				W
	Reverse Power					
	Peak Power					
Impedance		50				Ohms
Weight		NA				Ounces
Input / Output Connectors		2 . 9 2 m m – Female				
Material		Aluminum				
Finish		Oxidation sandblasting				

Environmental Specifications

Operational Temperature	-40°C~+85°C
Storage Temperature	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25gRMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions

Outline Drawing:

All Dimensions in mm (inches)

Outline Tolerances ± 0.5 (0.02)

Mounting Holes Tolerances ± 0.2 (0.008)

