

## Two-ways Coaxial Power Divider

P/N: YX-PD2-0.5G-6G

## Features

- It can realize the customized design scheme
- Excellent amplitude and phase consistency
- Low loss and High isolation



## Typical Applications

- Mobile communication field
- GSM,LTE,5G
- Satellite radar, electronic countermeasures
- Test equipment

## Electrical&Mechanical Specifications

Parameter		Min.	Typ.	Max.	Units	
Frequency Range		0.5		6	GHz	
Insertion Loss				4	dB	
Isolation		15	20		dB	
Input VSWR				1.4	: 1	
Output VSWR				1.4	: 1	
Amplitude Imbalance				±0.3	dB	
Phase Imbalance				±4	deg	
PowerRating	Forward Power	30				W
	Reverse Power	2				
	Peak Power	200 (15% Duty Cycle, 1 us Pulse Width)				
Impedance		50				Ohms
Weight		NA				Ounces
Input / Output Connectors		S M A – Female				
Material		Aluminum				
Finish		Oxidation sandblasting				

## Environmental Specifications

Operational Temperature	-40°C~+85°C
Storage Temperature	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25gRMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions

## Outline Drawing:

All Dimensions in mm (inches)

Outline Tolerances  $\pm 0.5(0.02)$

Mounting Holes Tolerances  $\pm 0.2(0.008)$

